

Listing of Claims:

1. (Currently Amended) A method of processing a request in a clustered computer system to organize a plurality of members into a group, the method comprising, in a local member from the plurality of members:

(a) locally determining within the local member whether the local member is a subgroup leader for a subgroup with which the local member is associated;
and

(b) if so, transmitting group data on behalf of the subgroup; and

(c) detecting in the local member whether the group data for the subgroup has already been transmitted by a previous subgroup leader, wherein transmitting the group data by the local member is performed only if the group data has not already been transmitted.

2. (Canceled)

3. (Currently Amended) ~~The method of claim 1, A method of processing a request in a clustered computer system to organize a plurality of members into a group, the method comprising, in a local member from the plurality of members:~~

~~— locally determining within the local member whether the local member is a subgroup leader for a subgroup with which the local member is associated;~~

~~— if so, transmitting group data on behalf of the subgroup; and~~

~~— detecting in the local member whether the group data for the subgroup has already been transmitted by a previous subgroup leader, wherein transmitting the group data by the local member is performed only if the group data has not already been transmitted; and wherein detecting whether the group data for the subgroup has already been transmitted by a previous subgroup leader includes~~

Page 2 of 12
Serial No. 09/697,398
Amendment After Final dated June 3, 2004
Reply to Office Action of May 7, 2004
IBM Docket ROC920000129US1
WH&E IBM/164
K:\ibm\164\Amendment After Final.wpd

accessing a local indicator that indicates whether the group data for the subgroup has already been transmitted, the method further comprising, in the local member:

clearing the local indicator in response to receipt of the request;

and

setting the local indicator in response to receipt of group data for the subgroup by the local member.

4. (Original) The method of claim 1, further comprising, in the local member:

(a) sending an acknowledgment message during an acknowledgment round;

(b) waiting for receipt of an acknowledgment message from each of the plurality of members; and

(c) processing the group data after receipt of acknowledgment messages from each of the plurality of members.

5. (Currently Amended) ~~The method of claim 4, further comprising, in the local member:~~ A method of processing a request in a clustered computer system to organize a plurality of members into a group, the method comprising, in a local member from the plurality of members:

locally determining within the local member whether the local member is a subgroup leader for a subgroup with which the local member is associated;

if so, transmitting group data on behalf of the subgroup;

sending an acknowledgment message during an acknowledgment round;

waiting for receipt of an acknowledgment message from each of the plurality of members;

processing the group data after receipt of acknowledgment messages from each of the plurality of members;

Page 3 of 12
Serial No. 09/697,398
Amendment After Final dated June 3, 2004
Reply to Office Action of May 7, 2004
IBM Docket ROC920000129US1
WH&E IBM/164
K:\bm\164\Amendment After Final.wpd

(a) receiving a message identifying a failed member among the plurality of members; and

(b) in response to receiving the message identifying the failed member, identifying the failed member, locally determining whether the local member is the subgroup leader for the subgroup subsequent to the failure of the failed member, and transmitting group data on behalf of the subgroup using the local member if the group data for the subgroup has not yet been transmitted.

6. (Original) The method of claim 5, wherein receiving the message identifying the failed member includes receiving a membership change message that is automatically generated responsive to failure of the failed member.

7. (Original) The method of claim 4, wherein sending the acknowledgment message is performed subsequent to the local member transmitting the group data on behalf of the subgroup if the local member is determined to be the subgroup leader, the method further comprising bypassing the transmitting of the group data by the local member if the local member is determined not to be the subgroup leader.

8. (Original) The method of claim 1, wherein locally determining within the local member whether the local member is the subgroup leader includes comparing a unique characteristic of the local member with those of the other members associated with the subgroup.

9. (Original) The method of claim 8, wherein the unique characteristic of the local member includes a member name, and wherein locally determining whether the local member is the subgroup leader includes determining whether the local member is the lowest named member among the members associated with the subgroup.

Page 4 of 12
Serial No. 09/697,398
Amendment After Final dated June 3, 2004
Reply to Office Action of May 7, 2004
IBM Docket ROC920000129US1
WH&E IBM/164
K:\brn\164\Amendment After Final.wpd

10. (Original) The method of claim 1, wherein the request comprises a join request, wherein the plurality of members is partitioned into first and second subgroups, the first group associated with existing members of the group, and the second subgroup associated with new members to be added to the group responsive to the join request.

11. (Original) The method of claim 1, wherein the request comprises a merge request, wherein the plurality of members is partitioned into a plurality of subgroups, each subgroup associated with a partition, and each partition associated with a subset of the plurality of the members.

12. (Currently Amended) A method of processing a request in a clustered computer system to organize a plurality of members into a group, the plurality of members partitioned into a plurality of subgroups, the method comprising:

(a) transmitting group data on behalf of each subgroup; and

(b) locally tracking within each member whether the group data for the subgroup associated with such member has been transmitted;

locally determining within each member whether the member is a subgroup leader for the subgroup with which the member is associated; and

if the member is a subgroup leader and the group data for the subgroup associated with the member has not been transmitted, transmitting with the member the group data on behalf of the subgroup.

13. (Canceled).

14. (Currently Amended) The method of claim 12, A method of processing a request in a clustered computer system to organize a plurality of members into a group, the plurality of members partitioned into a plurality of subgroups, the method comprising:

Page 5 of 12
Serial No. 09/697,398
Amendment After Final dated June 3, 2004
Reply to Office Action of May 7, 2004
IBM Docket: ROC920000129US1
WH&E IBM/164
K:\bm\164\Amendment After Final.wpd

~~transmitting group data on behalf of each subgroup;~~
~~locally tracking within each member whether the group data for the~~
~~subgroup associated with such member has been transmitted;~~
~~locally determining within each member whether the member is a~~
~~subgroup leader for the subgroup with which the member is associated; and~~
~~if the member is a subgroup leader and the group data for the subgroup~~
~~associated with the member has not been transmitted, transmitting with the~~
~~member the group data on behalf of the subgroup; wherein locally tracking within~~
~~each member whether the group data for the subgroup associated with such~~
~~member has been transmitted includes, for each member:~~
clearing a local indicator in response to receipt of the request; and
setting the local indicator in response to receipt of group data for
the subgroup associated with such member.

15. (Original) A method of processing a request in a clustered computer system to organize a plurality of members into a group, the plurality of members partitioned into a plurality of subgroups, the method comprising, for each subgroup:

- (a) determining a subgroup leader for such subgroup via a local determination made within each active member associated with such subgroup;
 - (b) determining within the subgroup leader for such subgroup whether group data has already been transmitted on behalf of such subgroup;
 - (c) if group data has not already been transmitted on behalf of such subgroup, transmitting the group data using the subgroup leader;
 - (d) performing an acknowledgment round to detect any failed members;
- and
- (e) repeating the determination of the subgroup leader for such subgroup, the determination of whether group data has already been transmitted, the

Page 6 of 12
Serial No. 09/697,398
Amendment After Final dated June 3, 2004
Reply to Office Action of May 7, 2004
IBM Docket ROC920000129US1
WH&E IBM/164
K:\lrm\164\Amendment After Final.wpd

transmission of the group data if no such group data has been transmitted, and the performance of the acknowledgment round until no failed members are detected in response to a last performed acknowledgment round.

16. (Currently Amended) An apparatus, comprising:

(a) a memory; and

(b) a program resident in the memory, the program configured to process a request in a clustered computer system to organize a plurality of members into a group by locally determining for a local member among the plurality of members whether the local member is a subgroup leader for a subgroup with which the local member is associated, and if so, transmitting group data on behalf of the subgroup, wherein the program is further configured to detect whether the group data for the subgroup has already been transmitted by a previous subgroup leader, and wherein the program is configured to transmit the group data only if the group data has not already been transmitted.

17. (Canceled).

18. (Currently Amended) The apparatus of claim 16. An apparatus, comprising:

(a) a memory; and

(b) a program resident in the memory, the program configured to process a request in a clustered computer system to organize a plurality of members into a group by locally determining for a local member among the plurality of members whether the local member is a subgroup leader for a subgroup with which the local member is associated, and if so, transmitting group data on behalf of the subgroup, wherein the program is further configured to detect whether the group data for the subgroup has already been transmitted by a previous subgroup leader;

Page 7 of 12
Serial No. 09/697,398
Amendment After Final dated June 3, 2004
Reply to Office Action of May 7, 2004
IBM Docket ROC920000129US1
WH&E IBM/164
K:\ibm\164\Amendment After Final.wpd

~~and wherein the program is configured to transmit the group data only if the group data has not already been transmitted; wherein the program is configured to detect whether the group data for the subgroup has already been transmitted by a previous subgroup leader by accessing a local indicator that indicates whether the group data for the subgroup has already been transmitted, and wherein the program is further configured to clearing the local indicator in response to receipt of the request and set the local indicator in response to receipt of group data for the subgroup.~~

19. (Original) The apparatus of claim 16, wherein the program is further configured to send an acknowledgment message during an acknowledgment round, wait for receipt of an acknowledgment message from each of the plurality of members, and process the group data after receipt of acknowledgment messages from each of the plurality of members.

20. (Original) ~~The apparatus of claim 19;~~ An apparatus, comprising:

(a) a memory; and

(b) a program resident in the memory, the program configured to process a request in a clustered computer system to organize a plurality of members into a group by locally determining for a local member among the plurality of members whether the local member is a subgroup leader for a subgroup with which the local member is associated, and if so, transmitting group data on behalf of the subgroup, wherein the program is further configured to send an acknowledgment message during an acknowledgment round, wait for receipt of an acknowledgment message from each of the plurality of members, and process the group data after receipt of acknowledgment messages from each of the plurality of members, and wherein the program is further configured to receive a message identifying a

Page 8 of 12
Serial No. 09/697,398
Amendment After Final dated June 3, 2004
Reply to Office Action of May 7, 2004
IBM Docket ROC920000129US1
WH&E IBM/164
K:\ibm\164\Amendment After Final.wpd

failed member among the plurality of members, and in response to receiving the message identifying the failed member, identify the failed member, locally determine whether the local member is the subgroup leader for the subgroup subsequent to the failure of the failed member, and transmit group data on behalf of the subgroup if the group data for the subgroup has not yet been transmitted.

21. (Original) The apparatus of claim 16, wherein the program is configured to locally determine whether the local member is the subgroup leader by determining whether the local member is a lowest named member among the members associated with the subgroup.

22. (Currently Amended) A clustered computer system, comprising:

- (a) a plurality of nodes coupled to one another over a network;
- (b) a plurality of member jobs defining a group and configured to be executed by at least one of the plurality of nodes; and
- (c) a program configured to be executed by at least one of the plurality of nodes to process a request received by a member job from the plurality of member jobs to add another member job to the group by locally determining for the member job whether the member job is a subgroup leader for a subgroup with which the member job is associated, and if so, transmitting group data on behalf of the subgroup, wherein the program is further configured to detect whether the group data for the subgroup has already been transmitted by a previous subgroup leader, and wherein the program is configured to transmit the group data only if the group data has not already been transmitted.

23. (Currently Amended) A program product, comprising:

(a) a program configured to process a request in a clustered computer system to organize a plurality of members into a group by locally determining for a local member among the plurality of members whether the local member is a subgroup leader for a subgroup with which the local member is associated, and if so, transmitting group data on behalf of the subgroup, wherein the program is further configured to detect whether the group data for the subgroup has already been transmitted by a previous subgroup leader, and wherein the program is configured to transmit the group data only if the group data has not already been transmitted; and

(b) a signal bearing medium bearing the program.

24. (Original) The program product of claim 23, wherein the signal bearing medium includes at least one of a recordable medium and a transmission medium.

Page 10 of 12
Serial No. 09/697,398
Amendment After Final dated June 3, 2004
Reply to Office Action of May 7, 2004
IBM Docket ROC920000129US1
WH&E IBM/164
K:\bm\164\Amendment After Final.wpd